Product Data Sheet

morrells
A Century of Coatings

Induro Mix&Fill Binder

Code	Description
2MF/104	Induro Mix&Fill Binder

Technical Data	A Cellulose based binding medium for mixing with sanding dusts to produce fast drying fillers for use in nail holes, splits/shakes and gaps between joints upto 5mm in width/depth.
Properties	Fillers prepared with this binder are easy to apply, fast drying and are easily sanded. Overcoatable with oils, water and solvent based flooring finishes.
Mixing Guidelines	1 part of the binding medium should be mixed with 1 – 2 parts of clean sanding dust from 80 – 120 grit sanding to produce a paste with a smooth consistency.
Application Guidelines	Preparation: • The flooring should be clean, dry and sanded back to bare timber. Application: • The filler should be applied over the whole area using a trowel, scraper or other straight edged tool. Ensure that holes, shakes and gaps are completely filled. • Allow to dry, typically 20 – 60 minutes, depending amount applied and the ambient conditions. When dry, sand with 100 -120 grit. • Repeat the application process if required. Using this product outside these guidelines can lead to immediate and latent problems with the integrity of the finish.
Important Information	➢ Failure to give the filler adequate drying can result in film defects and shrinkage after the lacquering process. ➢ Optimum application is achieved between 18°C and 22°C with good air movement and ventilation. ➢ Product should be stored above 5°C and protected from frost. ➢ Finished products should not be subjected to environments with temperatures of < 2°C. ➢ Out of scope with 2004/42/EC.
Health & Safety	Reference should be made to the appropriate MSDS for this product, which can be found at www.morrells.co.uk The use of appropriate personal protection equipment (PPE) is recommended. This product is intended for ***professional use*** only.